

Safety Data Sheet

TRUEGARD SAFETY SOLVENT

According to OSHA Hazard Communication Standard,
29 CFR 1910.1200 Effective Date 10/23/2018



P403+P235

P405

P501

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 3

COMPOSITION/INFORMATION ON INGREDIENTS

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt. %</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
Aliphatic hydrocarbon	64742-47-8	75-100	GHS07-GHS08	H227-304-315-336

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4

FIRST AID MEASURES



FIRST AID - EYE CONTACT: Immediately flush eyes with water. Flush eyes with water for a minimum of 15 minutes, occasionally lifting and lowering upper lids. Get medical attention promptly. Remove contact lenses if worn.

FIRST AID - SKIN CONTACT: Immediately wash with soap and water. Get medical attention promptly if irritation develops or persists. Remove contaminated shoes and clothes and clean before reuse.

FIRST AID - INHALATION: Rescuers should put on appropriate protective gear. Remove from area of exposure. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Keep victim warm. Get immediate medical attention.

FIRST AID - INGESTION: Small amounts which accidentally enter mouth should be rinsed out until taste of it is gone. Do not induce vomiting. Do not give liquids. Obtain emergency medical attention. To prevent aspiration, keep head below knees.

SECTION 5

FIRE FIGHTING MEASURES

UNUSUAL FIRE AND EXPLOSION HAZARDS: Combustible liquid and vapor. Vapors/dust may cause flash fire or explosion. Vapors can travel to a source of ignition and flash back. Empty containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. Also, do not reuse container without commercial cleaning or reconditioning.

SPECIAL FIREFIGHTING PROCEDURES: As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Avoid use of solid water streams. Use water spray to knock down vapors. Water spray to cool containers or protect personnel. Use with caution. Water spray and foam must be applied carefully to avoid frothing. Water runoff can cause environmental damage. Dike and collect water used to fight fire.

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Foam, Water Fog

SECTION 6

ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Wear appropriate personal protective equipment. (See Exposure Controls / Personal Protection Section.) Eliminate all ignition sources. Prevent additional discharge of material if able to do so safely. Do not touch or walk through spilled material. Avoid runoff into storm sewers and ditches which lead to waterways. Ventilate spill area. Stay upwind of spill. Use water mist or spray to disperse vapors. Collect spilled materials for disposal. Use only non-combustible material for clean-up. Use clean, non-sparking tools to collect absorbed materials. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container.

SECTION 7

HANDLING AND STORAGE



HANDLING: Use only in a well ventilated area. Avoid breathing vapor, fumes or mist. Avoid contact with eyes, skin, and clothing. Ground and bond containers when transferring material. Use spark-proof tools and explosion proof equipment. Always open containers slowly to allow any excess pressure to vent. Follow all MSDS/label precautions even after containers are emptied because they may retain product residues.

Safety Data Sheet

TRUEGARD SAFETY SOLVENT

According to OSHA Hazard Communication Standard,
29 CFR 1910.1200 Effective Date 10/23/2018



STORAGE: Keep away from heat, sparks, and flame. Store containers in a cool, well ventilated place. Keep container closed when not in use. Static Discharge, materials can accumulate static charges which can cause an incendiary electrical discharge. Material is a static accumulator which has the potential of forming ignitable vapor-air mixtures in storage tanks.

SECTION 8

EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with Occupational Exposure Limits

<u>Chemical Name</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH-TLV STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>
Aliphatic hydrocarbon	179 ppm	N.D.	N.D.	N.D.

Personal Protection



RESPIRATORY PROTECTION: A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits.



SKIN PROTECTION: Wear impervious protective gloves. Wear protective gear as needed - apron, suit, boots. Where contact is likely, wear chemical resistant gloves, a chemical suit, rubber boots, and chemical safety goggles plus a face shield.



EYE PROTECTION: Wear safety glasses with side shields (or goggles) and a face shield.



OTHER PROTECTIVE EQUIPMENT: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.



HYGENIC PRACTICES: Do not eat, drink, or smoke in areas where this material is used. Avoid breathing vapors. Remove contaminated clothing and wash before reuse. Wash thoroughly after handling. Wash hands before eating.

SECTION 9

PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Clear transparent liquid	Physical State:	Liquid
Odor:	Typical	Odor Threshold:	N.D.
Density, g/cm3:	0.801	pH:	N.D.
Freeze Point, °F:	N.D.	Viscosity:	N.D.
Solubility in Water:	Insoluble	Explosive Limits, vol%:	N.D.
Boiling Range, °F:	N.D.	Flash Point, °F:	153
Evaporation Rate:	N.D.	Auto-ignition Temp., °F:	N.D.
Vapor Density:	N.D.	Vapor Pressure:	N.D.

(See "Other information" Section for abbreviation legend)

SECTION 10

STABILITY AND REACTIVITY

STABILITY: No Information

CONDITIONS TO AVOID: Avoid impact, friction, heat, sparks, flame and source of ignition.

INCOMPATIBILITY: Prevent contact with strong oxidizing agents. Keep away from acids. Keep separate from alkalis.

HAZARDOUS DECOMPOSITION PRODUCTS: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

HAZARDOUS POLYMERIZATION: No Information

Safety Data Sheet

TRUEGARD SAFETY SOLVENT

According to OSHA Hazard Communication Standard,
29 CFR 1910.1200 Effective Date 10/23/2018



SECTION 11

TOXICOLOGICAL INFORMATION



Information on Toxicological Effects

Primary Route(s) of Entry: Eye Contact, Ingestion, Inhalation, Skin Contact

EFFECTS OF OVEREXPOSURE - INHALATION: Vapors can cause irritation to the respiratory tract. May cause central nervous system depression. Adverse symptoms may include the following: nausea or vomiting, headache, drowsiness/fatigue, dizziness/vertigo, unconsciousness. Causes delayed lung injury.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Causes skin irritation. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash). Personnel with pre-existing skin disorders should avoid contact with this product.

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Causes serious eye irritation. May cause tearing, redness and discomfort.

EFFECTS OF OVEREXPOSURE - INGESTION: Irritating to mouth, throat, and stomach. May be fatal if swallowed and enters airway. May cause central nervous system depression. May cause nausea and vomiting.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: Overexposure may cause nervous system damage. Small amounts of liquid aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary edema. Significant exposure to this chemical may adversely affect people with chronic disease of the respiratory system, skin, and/or eyes.

Carcinogenicity

<u>CAS-No.</u>	<u>Name</u>	<u>IARC</u>	<u>NTP</u>
64742-47-8	Aliphatic hydrocarbon	3- Not classifiable as to its carcinogenicity to humans.	Not Listed

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Name</u>	<u>Oral LD50, mg/kg</u>	<u>Dermal LD50, mg/kg</u>	<u>Vapor LC50, mg/L</u>
64742-47-8	Aliphatic hydrocarbon	>5000	>2000	>20

SECTION 12

ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: No Information

SECTION 13

DISPOSAL CONSIDERATIONS



For more guidance and information contact our Waste Services Division at (262) 658-4000.

Always dispose of any waste in accordance with all local, state, and federal regulations.

DISPOSAL METHOD: Dispose of waste in accordance with all local, state and federal regulations.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Wear appropriate personal protective equipment. (See Exposure Controls / Personal Protection Section.) Eliminate all ignition sources. Prevent additional discharge of material if able to do so safely. Do not touch or walk through spilled material. Avoid runoff into storm sewers and ditches which lead to waterways. Ventilate spill area. Stay upwind of spill. Use water mist or spray to disperse vapors. Collect spilled materials for disposal. Use only non-combustible material for clean-up. Use clean, non-sparking tools to collect absorbed materials. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container.

Safety Data Sheet

TRUEGARD SAFETY SOLVENT

According to OSHA Hazard Communication Standard,
29 CFR 1910.1200 Effective Date 10/23/2018



SECTION 14

TRANSPORT INFORMATION

DOT Proper Shipping
Name:

Not Regulated

Packing Group:

No Information

DOT Hazard Class:

No Information

Hazard SubClass:

No Information

DOT UN/NA Number:

No Information

Resp. Guide Page:

No Information

SECTION 15

REGULATORY INFORMATION

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No SARA 313 components exist in this product.

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA components exist in this product.

U.S. State Regulations:

NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product.

No NJ Right-To-Know components exist in this product.

PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product at greater than 3%.

No PA Right-To-Know components exist in this product.

CALIFORNIA PROPOSITION 65 CARCINOGENS

Warning: The following ingredients present in the product are known to the state of California to cause Cancer.

No Proposition 65 Carcinogens exist in this product.

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

No Proposition 65 Reproductive Toxins exist in this product.

International Regulations: As follows -

CANADIAN WHMIS:

This SDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

WHMIS Class:

No Information

Safety Data Sheet

TRUEGARD SAFETY SOLVENT

According to OSHA Hazard Communication Standard,
29 CFR 1910.1200 Effective Date 10/23/2018



SECTION 16

OTHER INFORMATION

Revision Date: 10/23/2018

Supersedes Date:

New SDS

Datasheet produced by: EH&S - Regulatory Department

HMIS Ratings:

Health: 1 Flammability: 2 Reactivity: 0 Personal Protection: X

Volatile Organic Compounds, gr/ltr: 799

DISCLAIMER: THE VOLATILE ORGANIC COMPOUND (VOC) CONTENT REPORTED HEREIN, IF ANY, IS BASED ON A MATERIAL VOC CALCULATION. NOTE THAT SEVERAL METHODS ARE USED FOR CALCULATING VOC CONTENT AND THAT STANDARDS/ REQUIREMENTS REGARDING VOC CONTENT VARY BY LOCATION/JURISDICTION. ACCORDINGLY, EMCO MAKES NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED, REGARDING THIS MATERIAL'S COMPLIANCE WITH VOC STANDARDS/ REQUIREMENTS APPLICABLE IN LOCATIONS/JURISDICTIONS WHERE THIS MATERIAL MAY BE SOLD OR USED.

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H227	Combustible liquid
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:

GHS07



GHS08



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

The information on this SDS was obtained from sources which we believe to be reliable. However, the information provided is without any warranty, expressed or implied, regarding its correctness. Some information presented and conclusions drawn herein are from sources other than direct test data on the product itself. The information and recommendations are offered for the user's consideration and examination and should be used to make an independent determination of the methods to safeguard workers and the environment. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For these reasons we do not assume responsibility and expressly disclaim any liability for loss, damage, or expense arising out of or in any way connected with handling, storage, use, or disposal of this product. If the product is used as a component in another product, this SDS may not be applicable. It is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.

Safety Data Sheet

TRUEGARD SAFETY SOLVENT

According to OSHA Hazard Communication Standard,
29 CFR 1910.1200 Effective Date 10/23/2018

Keller-Heartt Oil
Oil solutions for today and tomorrow...

TRUEGARD

SECTION 1

MATERIAL AND COMPANY IDENTIFICATION

Material Name: TRUEGARD SAFETY SOLVENT

Information Phone: 773-247-7606

Emergency Phone: Poison Control Center: Consult local
telephone directory for emergency number(s).

Supplied by:

KELLER-HEARTT OIL
4411 South Tripp Ave.
Chicago, IL 60632
P. 773-247-7606 F. 773-247-7969
www.kellerheartt.com

SECTION 2

HAZARDS IDENTIFICATION

***** EMERGENCY OVERVIEW ***:** Combustible liquid and vapor. May be fatal if swallowed and enters airway.

GHS Classification

Asp. Tox. 1, Flam. Liq. 4, Skin Irrit. 2, STOT SE 3 NE

Symbol(s) of Product



Signal Word

Danger

GHS HAZARD STATEMENTS

Flammable liquid, category 4	H227	Combustible liquid
Aspiration Hazard, category 1	H304	May be fatal if swallowed and enters airways.
Skin Irritation, category 2	H315	Causes skin irritation.
STOT, single exposure, category 3, NE	H336	May cause drowsiness or dizziness.

GHS PRECAUTIONARY STATEMENTS

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician
P302+P352	IF ON SKIN: Wash with plenty of water
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor/physician if you feel unwell.
P321	Specific treatment (see first aid section on this label).
P331	Do NOT induce vomiting.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire: Use appropriate method to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.